

Photometric Report

SAM0904920005 Track light 30W (NW), , Ordercode

REPORT SUMMARY

Output

Total Lumens:	2265 Lumen
Peak Intensity:	4111 candela
Illuminance @ 5m:	164 lx
CRI:	95,1
CCT:	4046 K



Optical


Beam Angle (50%)	38,6 °
Field Angle (10%)	70,5 °

Conditions:


Power Supply:	223 V
Power:	29,3 W
Current:	0,133 A
Power Factor:	0,99

MEASUREMENTS


Angular Beam Distribution



Spectral Distribution



CIE 1931




Photometric Report




SAM0904920005 Track light 30W (NW), , Ordercode

BEAM DETAILS



Beam Illuminances from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3,3ft	6,6ft	9,8ft	13,1ft	16,4ft	19,7ft	23ft	26,2ft	29,5ft	32,8ft	36,1ft	39,4ft	42,7ft	45,9ft	49,2ft	52,5ft	55,8ft	59,1ft	62,3ft	65,6ft
4109lx	1027lx	457lx	257lx	164lx	114lx	84lx	64lx	51lx	41lx	34lx	29lx	24lx	21lx	18lx	16lx	14lx	13lx	11lx	10lx
381,8fcd	95,4fcd	42,4fcd	23,9fcd	15,3fcd	10,6fcd	7,8fcd	6fcd	4,7fcd	3,8fcd	3,2fcd	2,7fcd	2,3fcd	1,9fcd	1,7fcd	1,5fcd	1,3fcd	1,2fcd	1,1fcd	1fcd




Beam Angle (50%): 38,6 °
 Field Angle (10%): 70,5 °
 Cutoff Angle (3%): 103,6 °

Photometric Report



SAM0904920005 Track light 30W (NW), , Ordercode

POLAR DIAGRAMS




ISO candela diagram

10%	411 cd
20%	822 cd
30%	1233 cd
40%	1644 cd
50%	2055 cd
60%	2466 cd
70%	2877 cd

Conditions:

Number of c-planes: {C_PLANES}

Candela at center: 4109 cd



ISO lux diagram

3%	1,23 lx
5%	2,05 lx
10%	4,11 lx
30%	12,3 lx
50%	20,5 lx

Conditions:

Number of c-planes: 2

Lux at center: 41,1 lx

Lux distribution on a surface when lamp is mounted at 10 meters from the surface.

Mounting height: 10 meters (33 feet)

Photometric Report



SAM0904920005 Track light 30W (NW), , Ordercode


CHROMATICITY REPORT

Total Lumens: 2265 lm
Peak Intensity: 4111 cd
Fixture Efficiency: 77 Lumen/Watt

Color Temperature: 4046 K
CRI: 95,1
CRI R9: 77,7
CQS: 93,7
TM-30 Rf: 92,4
TM-30 Rg: 101,6
 Δuv : -0,0080
1st Dominant Wavelength: 448 nm
2nd Dominant Wavelength: 612 nm



Spectral Distribution



Color

4046 K
CIE 1931 Coordinates:
X: 0,373 Y: 0,356

Color Temperature

4046 K

CRI

95,1


Photometric Report




SAM0904920005 Track light 30W (NW), , Ordercode

CHROMATICITY


CIE 1931




CIE 1931 - Detail



CRI: 95,1 (R1-R8)



CQSI: 93,7



Photometric Report




SAM0904920005 Track light 30W (NW), , Ordercode

TM-30-18 DETAILS


Rf 92,4
Fidelity index Rf

Rg 101,6
Gamut index Rg


Hue Bin	R _f	Shifts (%)	
		Chroma	Hue
1	93	-3%	0%
2	95	-1%	2%
3	93	0%	3%
4	95	-1%	1%
5	94	-1%	1%
6	96	2%	1%
7	96	0%	1%
8	94	0%	3%
9	93	1%	5%
10	92	0%	5%
11	88	5%	7%
12	89	5%	2%
13	90	5%	-5%
14	95	3%	-1%
15	88	1%	-7%
16	88	0%	-7%



TM30-18 Color Vectors




Rf by Hue Bin



TM30 Color Distortion



TM30 Chroma Shift



TM30 Color Fidelity Sample Chart

