

AUDIO SPECIFICATIONS

FREQUENCY RANGE

45-20,000 Hz

STEREO/MONO

MONO

MAXIMUM SOUND PRESSURE LEVEL

118 dB (RMS), 121 dB (Peak)

CABINET PRINCIPLE

Bass Reflex

POWER AMPLIFIERS

140W (RMS), 400W (Peak) Class D

SPEAKERS

1x10-inch woofer, 2x1-inch tweeter

TOTAL IMPEDANCE

4 ohms

Power

MAIN INPUT POWER

AC 100-240V

DC POWER OUTPUT For Spark 2 & Spark 40

DC 20V/2.5A

USB-C POWER OUTPUT For Spark MINI, GO & PEDAL

DC 5V/2A

CONTROLS AND CONNECTIVITY

BACK PANEL CONTROLS

Input Selector - Switch between the 3.5 mm Spark Input and the two mono XLR/TRS Combo Inputs

Speaker Volume

Line Out Volume

Ground Lift Switch

Contour Switch - Boosts low and high frequencies to improve balance at low volumes

WIRED CONNECTIVITY

1 x 3.5mm dedicated stereo Input for Spark Amp
2 x mono XLR/TRS combo inputs
1 x mono XLR balanced output

INCLUDED IN THE BOX**BOX CONTENTS**

- Spark CAB 2
- Quick Start Guide
- AC Power Cord
- DC Power Cable
- DC Power Cable Adapter for Spark 2
- 3.5mm Audio Stereo Cable

PHYSICAL UNIT**DIMENSIONS**

492.5 x 399.8 x 255 mm (with rubber feet)
(19.39 x 15.74 x 10.04 in)

WEIGHT

13.5 kg
29.76 lbs

GRILLE CLOTH

Woven

Handle

2 recessed speaker handles on the sides

Cable Tie

1 adjustable cable tie for fixing instrument and audio cables on the back